ตู้เย็นสำหรับห้องปฏิบัติการ
อุณหภูมิ 2-8°C

Laboratory Refrigerator

- Precision Cooling
- Smart Control
- Reliable Protection



Accuplus P280

Temperature Control

Programmable Controller
Forced-air circulation system ensuring constant cabinet temperature
Temperature setting range can selected by user from 2 - 8 °C

Ergonomic Design

Multilevel adjustable shelves
LED display for easy observation
R290 refrigerant
Inner light
4 castors easy to move

Alarm and safety function

Audible and visible alarms
Upper/Lower alarm
Data Logging: Real-time temperature logging and remote app control (Optional)

ตู้เย็นสำหรับห้องปฏิบัติการ

อุณหภูมิ 2-8 °C
Laboratory Refrigerator

Technical Data

Accuplus P280

Capacity	280 Liters (9 Cu.ft)
Temperature Control	Programmable Controller
Application Control	Remote temperature setting, control, and monitoring via the Application(Option)
Temperature Range	2 - 8˚C with 0.1˚C Resolution
Temperature Stability	± 2.0°C
Display	LED
External Material	Powder coated metal
Internal Material	Powder coated metal
Alarm	Audible and visible alarms Upper / Lower alarms
Door Type	2 layer glass doors
Inner Light	LED x 1 set
Shelves	5 adjustable shelves
Drainage System	Maintenance-free auto-evaporation system
Security System	ELCB (Earth leakage circuit breaker) system
Legs / Caster Wheel	Equipped with 4 castors with 2 stoppers
Refrigerant	R290
Dimension (W x D x H)	Internal : 495 x 495 x 1170 mm. External : 595 x 590 x 1900 mm.
Power Supply	220-240 V / 50 Hz.
Factory Certification	ISO 9001:2008 Certified
Warranty	1 year

